




Essence FR



WHITE - 11



WHITE/SAND - 14



WHITE/PEARL - 12



PEARL - 22



GREY/BLACK - 52




BRONZE/BLACK - 58



BLACK - 55



Essence FR





ESSENCE FR Technical features

TEST	VALUE	UNIT
Composition	30% Polyester - 70% Pvc	
Available widths	2500* - 3000	mm
Roll size roller	30	lmt
Color fastness	7	DIN EN ISO 105-B01:2014
Cutting method	Cold cut	

1% Openness factor				
Weight	480	gr/m ² sqmt		
Thickness	0,68	mm		
UV screening	97%			
Color	Ts%	Rs%	As%	Tv%
White - 11	24	64	12	20
White/Sand - 14	17	55	28	12
White/Pearl - 12	12	43	45	9
Pearl - 22	9	35	56	4
Grey/Black - 52	2	8	90	1
Bronze/Black - 58	2	7	91	1
Black - 55	1	3	96	1

3% Openness factor				
Weight	430	gr/m ² sqmt		
Thickness	0,62	mm		
UV screening	94%			
Color	Ts%	Rs%	As%	Tv%
White - 11	24	63	13	21
White/Sand - 14	23	58	19	18
White/Pearl - 12	16	42	42	12
Pearl - 22	9	32	59	4
Grey/Black - 52	4	10	86	4
Bronze/Black - 58	5	7	88	4
Black - 55	3	3	94	3

5% Openness factor				
Weight	410	gr/m ² sqmt		
Thickness	0,55	mm		
UV screening	90%			
Color	Ts%	Rs%	As%	Tv%
White - 11	29	60	11	26
White/Sand - 14	27	54	19	22
White/Pearl - 12	17	38	45	13
Pearl - 22	18	34	48	14
Grey/Black - 52	10	12	78	9
Bronze/Black - 58	10	8	82	9
Black - 55	8	3	89	8



*2500 On request