



WHITE - 001



CREAM - 003



LIGHT GREY - 002



DARK GREY - 010



BLACK - 005



Reflex FR



newblinds.co.uk

Reflex FR

REFLEX FR Technical features

TEST	VALUE	UNIT
Composition	100% Polyester	
Weight	300	g / m ²
	0,64	mm
Available widths	2400	mm
Vertical louvre widths	89 - 127	mm
Roll size vertical	150	lmt
Roll size roller	30	lmt
Color fastness	6 - 7	DIN EN ISO 105-B01:2014
Openness factor	3%	
Transparency	Transparent	
Cutting method	Ultrasonic / Hot cut	
Reference	EN.REF.240.XXX - H240 width	
Reference	VE.REF.089.XXX - H089 width	
Reference	VE.REF.127.XXX - H127 width	

COLORS	AVAILABLE WIDTH			SOLAR AND OPTICAL FEATURES					
	2400 mm	89 mm	127 mm	R Solar Reflexión %	T Solar Transmission %	A Solar Absorption %	Total energy Transmission gi	Reduce Factor Fc	VIS Energy rating
WHITE - 001	•	•	•	61	5	34	0,38	0,55	2
CREAM - 003	•	•	•	65	5	30	0,36	0,52	2
LIGHT GREY - 002	•	•	•	63	3	34	0,37	0,53	2
DARK GREY - 010	•	•	•	63	2	35	0,37	0,53	2
BLACK - 005	•	•	•	66	2	43	0,40	0,58	2



FIRE RESISTANT DIN - 4102

- 100% Polyester
- Transparent
- Clean with damp cloth
- PVC free

- 300 g / m²
- Suitable for computer screens
- Lightfast



ROLLER



PANEL



VERTICAL



FIRE RESISTANT DIN - 4102



ROLLER



PANEL



VERTICAL



newblinds.co.uk