

Key Button/ Switch FMT



Key Button/ Switch FMT

Art.-no.: 50000013

Safety Precautions

- Contact a professional electrician to install the control system, because the control system requires a power supply of 230VAC, 50 Hz.
- the control system requires a power supply of 230VAC, 50 Hz.

 Check the control system for signs of mechanical damage after unpacking. If you notice any shipping damage, do not start up the control system and notify your supplier immediately.

 The control system should only be used for the purpose specified by the manufacturer (refer to the operating instructions). Any changes or modifications thereof are not permissible and will result in loss of all warranty claims.
- If the control unit cannot be operated without presenting a hazard, it must be switched off and prevented from being switched on uninten-tionally.
- When performing work on the windows, controls or connected shades, protect them against unauthorised or unintentional operation.

Assembly and installation

Side Projection

WARNING! Risk of injury due to improper installation and commissioning.

Improper installation and commissioning may lead to personal injury or property damage.

When connecting the device, observe the currently valid VDE standards (in particular DIN VDE 0100/0700), your local power company's regulations and the current accident prevention regulations.

Rear Assembly



Technical Data

Permissible current: 10A Dimensions (L × W × H): 81mm x 81mm x 25mm

Mounting Centres: 60mm

25mm Rear projection: